


impression









THE IMPRESSION X4S WHITE IN BRIEF

The Impression X4S features 7 high power CwWw LEDs, each rated at 15W, with a 7 $^{\circ}$ - 50 $^{\circ}$ zoom range. Using the same optics as the Impression X4, the X4S features the same characteristics of a well defined hard edged beam at the lower zoom range, with a homogeneous and soft edged beam at wider angles. Being smaller and lighter, the X4S features fast pan and tilt movement with 16 bit control.

LIGHT SOURCE 7 High Power CwWw LEDs Cold White: 10000K (CRI:74) Warm White: 2700K (CRI:94)

OPTICAL SYSTEM

Motorized zoom system with 7° to 50° beam angle High efficiency collimator cluster for maximum light output

MOVEMENT

8 or 16 bit resolution Position feedback Maximum speed: 660° pan in 2 sec 260° tilt in 1 sec High precision 3 phase stepping motor control

SHUTTER / DIMMER Continuous dimmer 0-100% Variable speed strobe of 1-25 Hz. Random strobe effect Pulse effects CONTROL DMX-512 protocol Macro operation of individual lenses Very quiet temperature controlled ventilation system Convection cooling option Variable color temperature control from 2500K-10000K Backlit graphic LCD menu Over-temperature protection

POWER SUPPLY Power input: Auto sensing 100-240 VAC / 50-60Hz Power consumption: 150 Watt max. Fuse protection: Microfuse 20mm, T 2A

CONNECTORS DMX: XLR 5 pin Mains voltage: Neutrik Powercon OPERATING CONDITIONS Maximum ambient temperature: 113°F / 45°C

MOUNTING OPTIONS 3 M10 sockets for half coupler or other clamp 2 attachment points for safety wires

SHIPPING

Cardboard box 4 way tourpack (complete with half couplers) in flight case 8 way tourpack (complete with half couplers) in flight case

HOUSING COLORS Standard colors are black, silver and white

black, silver and white For other colors please contact sales department DIMENSIONS Length x width x height (head vertical): 6.4 x 8.5 x 12 inches / 220mmx155mmx310 mm

NET WEIGHT 12 lbs / 5.2 kg





 GLP German Light Products, Inc

 10945 Pendleton Street

 Sun Valley, CA 91352

 Phone:
 +1 818 767 8899

 Fax:
 +1 818 279 9898

 Mail:
 usa@glp.de

Web: www.germanlightproducts.com

www.germanlightproducts.com





