

# X4 atom Variable White Version



The GLP X4 Atom has been designed from the ground up to be a new standard in versatile lighting fixtures, and is now available in variable white, along with the original RGBW version.

With its small body, designed to fit subtly into the tightest spaces yet give big coverage, the X4 Atom is a new everyday fixture.

The variable white version of the X4 Atom is fitted with the a high output LED source with both warm and cold color elements allowing a variable range from 2700K to 10000K.

But the X4 Atom houses a lot more, starting with a 9 to 1 ratio zoom that goes from a wide 34° wash down to a tight 3.5° beam for pinpoint accuracy and great mid-air effects.

As versatility is the key, we made the housing IP 65 rated allowing it to be used on events and shows all year round, indoors or out.

For times when one X4 Atom just isn't enough, we've created a fast interlock system that allows fixtures to easily be coupled together.

The standard yoke is easily removed and you can quickly assemble pairs, quads, lines and grids of fixtures in any configuration that you need – and still keep individual control of each Atom, creating stunning displays.

The X4 Atom runs from an external power supply that feeds fixtures via an industry standard 4 pin XLR cable, tapping into existing infrastructure and reducing the overall environmental impact of the Atom.



# X4 atom



## TECHNICAL DATA

### X4 ATOM HEAD

#### LIGHT SOURCE

1 High power CW/WW LED  
Cold White: 10000K (CRI:74)  
Warm White: 2700K (CRI:94)  
50,000 hour rated life

#### OPTICAL SYSTEM

Motorized zoom system with 3.5° to 34° beam angle  
High efficiency collimator cluster for maximum output

#### SHUTTER / DIMMER

Continuous Dimmer 0-100%  
Variable speed strobe of 1-10 Hz.  
Random Strobe Effect  
Pulse Effects

#### CONTROL

DMX 512 Control  
Internal color pallets  
Very quiet temperature controlled ventilation system  
Over temperature protection

#### CONNECTORS

4 pin XLR

#### OPERATING CONDITIONS

IP 65 Rated  
Maximum ambient temperature: 45° C / 113° F

#### MOUNTING OPTIONS

Combined floor / hanging bracket included  
Additional options through Connect Module adaptor

#### SHIPPING

Cardboard Box

#### HOUSING COLORS

Black  
For other colors, please contact sales department

#### DIMENSIONS

Without yoke attached:  
5 x 5 x 6.63in / 12.7 x 12.7 x 16.9cm (length x width x height)

With yoke attached:  
5 x 7 x 9.75in / 12.7 x 17.8 x 24.8cm (length x width x height)

#### NET WEIGHT

without - 3lbs. / 1.4kg  
with - 4lbs./ 1.8kg

## TECHNICAL DATA

### X4 ATOM PSU

#### CONTROL

DMX 512 protocol  
Backlit Graphic LCD Menu for addressing fixtures and setting other options

#### POWER SUPPLY

Power input:  
90-240 VAC / 50-60 Hz.  
Power consumption: 20VA (Watt), per X4 Atom Head

#### OPERATING CONDITIONS

IP20 rated  
Maximum ambient temperature: 45° C / 113° F

#### CONNECTORS

Neutrik PowerCon In and Thru  
DMX: XLR 5 pin  
Atom head output: 12 x 4 pin XLR

#### MOUNTING OPTIONS

M10 socket for direct half coupler  
Omega bracket attachment points  
2 attachment points for safety wires

#### SHIPPING

Cardboard Box

#### HOUSING COLORS

Black

#### DIMENSIONS

12.38 x 7.75 x 4.25in / 31.4 x 19.7 x 10.8cm (length x width x height)

#### NET WEIGHT

9lbs. / 4.1kg



**GLP German Light Products, Inc**

10945 Pendleton Street

Sun Valley, CA 91352

Phone: +1.818.767.8899

Fax: +1.818.279.9898

Mail: [info@germanlightproducts.com](mailto:info@germanlightproducts.com)

Web: [www.germanlightproducts.com](http://www.germanlightproducts.com)