



impression[®]
X1

COMPACT AND FAST INFINITE-PAN/-TILT MOVING HEAD



The impression X1 differs from other products in GLP's X range, by featuring 4 high powered, 15 Watt, RGBW LED's with a narrow fixed beam output that offers continuous pan and tilt motion, in a compact housing.

The fixed beam optics are interchangeable between

different beam angles from the standard 7 degrees. The compact base of the impression X1 houses Neutrik PowerCON in and thru connectors for easy daisy chaining of multiple fixtures, whilst the power supply is fully auto sensing from 100-240 V, 50/60 Hz.



Lighting design Pallo Palmé

TECHNICAL DATA

LED-SOURCE

LED-Type	Osram Ostar
Lifetime (Hours)	50,000
LED count	4
LED colors	RGBW

OPTICS

Fixed Optics	7° (interchangeable)
--------------	----------------------

MOVEMENT

Resolution	8 - 16 Bit
Position Feedback	Yes
Pan	660°
Tilt	300°
Continuous Movement	360° Pan & Tilt

CONTROL

Control-Modes	Normal Compressed
Display	Backlit graphic LCD
Protocol	USITT DMX-512
Cooling	Temperature controlled Overheating protection

EFFECTS

Dimmer	0-100% electronic
Shutter	Max. 14 Hz electronic

CONNECTORS

Signal connection	XLR 5-Pin In/Out
Power Input	Neutrik powerCON In/Out

OPERATING CONDITIONS

Mains voltage	100-240 VAC / 50-60Hz
Power (Watt @ 230V)	100 W
Fuse	20mm T 2A
Max. ambient temperature	45°C / 115°F
Orientation	Any
EEC	C
EEL	0.742
Ec (kWh/1.000h)	69

INSTALLATION

Standing	Rubber feet
Safety wire attachment	2 eyelets
Hanging (vertical)	M10 socket for half coupler or other clamp

SHIPPING

Single fixture	Cardboard
Tourpack	6-way 12-way Flightcase

HOUSING COLORS

Standard color	Black
Optional	Special colors on request

DIMENSIONS & WEIGHT

Length	195 mm / 7.6 in
Width	140 mm / 5.5 in
Height (Head vertical)	255 mm / 12.2 in
Weight	3.1 kg / 6.8 lbs

CONTINUOUS



When size matters