



KNV LINE



LIGHT SOURCE

| | |
|----------|--|
| Type | 5 hyper bright 30W white LEDs surrounded by 16 RGB LED's |
| Lifetime | 50,000 hours |
| Output | Up to 11,000lm total |

CONTROL

| | |
|-----------|--|
| Protocols | DMX, ArtNet, sACN |
| 7 Modes | 10, 23, 35, 40, 86, 102 & 201 channels |
| PWM | Variable, up to 38kHz |

DYNAMIC EFFECTS

| | |
|------------|---------------------------------------|
| Color | 16 bit RGBW |
| Dimmer | 16 bit electronic dimming |
| Strobe | intensity, flash rate, flash duration |
| FX Engines | Powerful 3 layer FX engine |

OPERATING CONDITIONS

| | |
|-------------------|---------------------------------------|
| External PSU | Supports Max. 5 KNV lines |
| Power (Watt@230V) | 5 RGB (16x 0.25W) 5 White (1x 30W) |

INSTALLATION

| | |
|-------------|--|
| Mounting | Individual floorstand Individual hanging yoke Coupling plates to create freeform frameless designs |
| IP rating | IP54 |
| Orientation | Any |

DIMENSIONS & WEIGHT

| | |
|--------|------------|
| Width | 9.8in/38cm |
| Height | 2in/26.6cm |
| Depth | 6.5in/18cm |
| Weight | 4lbs/1.8kg |