

DMX Channel Index

HIGHLANDER

WASH



Fixture software version 26



GLP® Highlander Wash DMX Channel Index – Revision A (this revision is preliminary)
This document covers fixture software version 26

© 2019 German Light Products GmbH. All rights reserved.

The marks 'GLP' and 'German Light Products' are trademarks registered as the property of German Light Products GmbH in Germany, in the United States of America and in other countries.

The information contained in this document is subject to change without notice. German Light Products GmbH and all affiliated companies disclaim liability for any injury, damage, direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document.

Manufacturer's head office:

German Light Products GmbH (GLP), Industriestrasse 2, 76307 Karlsbad, Germany

Tel (Germany): +49 7248 92719 - 0

Service & Support EMEA:

GLP, Industriestrasse 2, 76307 Karlsbad, Germany

Tel. (Germany): +49 7248 9271955

Email: support@glp.de

www.glp.de

Service & Support USA:

GLP USA, 1145 Arroyo St., Ste. A, 91340 San Fernando, California

Tel (USA): +1 818 767 8899

Support (US): info@germanlightproducts.com

www.germanlightproducts.com

1. DMX control layout

Normal Mode (26 DMX channels)

Channel	Function	Description	DMX range	Default DMX	% Range	Fade
1	Pan coarse	-320° – +320° (16-bit)	0 – 65535	32767	0 – 100%	Fade
2	Pan fine					
3	Tilt coarse	-131° – +131° (16-bit)	0 – 65535	32767	0 – 100%	Fade
4	Tilt fine					
5	Color wheel 1	Open	0 – 5	0	0 – 2.0%	Snap
		Color 1 – Deep red	6 – 10		2.4 – 3.9%	Snap
		Color 2 – Blue	11 – 15		4.3 – 5.9%	Snap
		Color 3 – Deep green	16 – 20		6.3 – 7.8%	Snap
		Color 4 – Light green	21 – 25		8.2 – 9.8%	Snap
		Color 5 – Yellow	26 – 30		10.2 – 11.8%	Snap
		Color 6 – Orange	31 – 35		12.2 – 13.7%	Snap
		Color 7 – Deep blue	36 – 40		14.1 – 15.7%	Snap
		Open	41 – 43		16.1 – 16.9%	Snap
		Color wheel indexing 0 – 360° (continuous)	44 – 167		17.3 – 65.5%	Fade
		Color wheel rotation CW fast – slow	168 – 211		65.9 – 82.7%	Fade
Color wheel rotation stop	212	83.1%	Snap			
Color wheel rotation CCW slow – fast	213 – 255	83.5 – 100%	Fade			
6	Color wheel 2	Open	0 – 5	0	0 – 2.0%	Snap
		Color 1 – Lavender	6 – 10		2.4 – 3.9%	Snap
		Color 2 – Magenta	11 – 15		4.3 – 5.9%	Snap
		Color 3 – Pink	16 – 20		6.3 – 7.8%	Snap
		Color 4 – Half minus green	21 – 25		8.2 – 9.8%	Snap
		Color 5 – CTB	26 – 30		10.2 – 11.8%	Snap
		Color 6 – CTO	31 – 35		12.2 – 13.7%	Snap
		Color 7 – Amber	36 – 40		14.1 – 15.7%	Snap
		Open	41 – 43		16.1 – 16.9%	Snap
		Color wheel indexing 0 – 360° (continuous)	44 – 167		17.3 – 65.5%	Fade
		Color wheel rotation CW fast – slow	168 – 211		65.9 – 82.7%	Fade
Color wheel rotation stop	212	83.1%	Snap			
Color wheel rotation CCW slow – fast	213 – 255	83.5 – 100%	Fade			
7	Cyan	Cyan 0 – 100%	0 – 255	0	0 – 100%	Fade
8	Magenta	Magenta 0 – 100%	0 – 255	0	0 – 100%	Fade
9	Yellow	Yellow 0 – 100%	0 – 255	0	0 – 100%	Fade
10	CTO	CTO 0 – 100%	0 – 255	0	0 – 100%	Fade
11	Shutter	Shutter closed	0 – 15	255	0 – 5.9%	Snap
		Pulse, random, slow – fast	16 – 47		6.3 – 18.4%	Fade
		Pulse, slow – fast	48 – 79		18.8 – 31%	
		Pulse open, slow – fast	80 – 111		31.4 – 43.5%	
		Pulse close, slow – fast	112 – 143		43.9 – 56.1%	
		Strobe, random, slow – fast	144 – 199		56.5 – 78.0%	
		Strobe, 1 – 10 Hz	200 – 239		78.4 – 93.7%	
		Shutter open	240 – 255		94.1 – 100%	Snap

12	Dimmer coarse	Intensity 0 – 100%	0 – 65535	32768	0 – 100%	Fade
13	Dimmer fine					
14	Zoom	Narrow (spot) – wide (flood)	0 – 255	128	0 – 100%	Fade
15	Focus	Near – far	0 – 255	128	0 – 100%	Fade
16	Framing module indexing	CW indexing from 0° to -45° Center: 0° CCW indexing from 0° to +45°	0 – 128 128 129 – 255	128	0 – 50.2% 50.2% 50.6 – 100%	Fade Snap Fade
17	Framing blade 1 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
18	Framing blade 1 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
19	Framing blade 2 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
20	Framing blade 2 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
21	Framing blade 3 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
22	Framing blade 3 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
23	Framing blade 4 position / left	PI mode: In – out LR mode: Blade left side	0 – 255 0 – 255	0 0	0 – 100% 0 – 100%	Fade Fade
24	Framing blade 4 index / right	PI mode: Tilt -30° – +30° LR mode: Blade right side	0 – 255 0 – 255	128 0	0 – 100% 0 – 100%	Fade Fade
25	Iris effect	Open – closed	0 – 255	128	0 – 100%	Fade

26	Special/Control	No function	0 – 26	0	0 – 10.2%	Snap
		Performance fast*	27 – 29		10.6 – 11.4%	
		Performance normal*	30 – 32		11.8 – 12.5%	
		Performance smooth*	33 – 35		12.9 – 13.7%	
		No function	36 – 38		14.1 – 14.9%	
		Dimmer curve soft*	39 – 41		15.3 – 16.1%	
		Dimmer curve linear*	42 – 44		16.5 – 17.3%	
		No function	45 – 53		17.6 – 20.8%	
		Display off*	54 – 56		21.2 – 22%	
		Display auto-off*	57 – 59		22.4 – 23.1%	
		Display on*	60 – 62		23.5 – 24.3%	
		Display orientation normal*	63 – 65		24.7 – 25.5%	
		Display orientation invert*	66 – 68		25.9 – 26.7%	
		Display orientation auto*	69 – 71		27.1 – 27.8%	
		No DMX = blackout*	72 – 74		28.2 – 29.0%	
		No DMX = hold*	75 – 77		29.4 – 30.2%	
		No DMX = play stand-alone*	78 – 80		30.6 – 31.4%	
		Capture stand-alone scene (DMX snapshot)*	81 – 83		31.8 – 32.5%	
		No function	84 – 86		32.9 – 33.7%	
		Fan regulated*	87 – 89		34.1 – 34.9%	
		Fan high speed*	90 – 92		35.3 – 36.1%	
		No function	93 – 104		36.5 – 40.8%	
		Position feedback off*	105 – 107		41.2 – 42.0%	
		Position feedback on*	108 – 110		42.4 – 43.1%	
		Effect shortcuts off*	111 – 113		43.5 – 44.3%	
		Effect shortcuts on*	114 – 116		44.7 – 45.5%	
		Tilt invert off*	117 – 119		45.9 – 46.7%	
		Tilt invert on*	120 – 122		47.1 – 47.8%	
		Pan invert off*	123 – 125		48.2 – 49.0%	
		Pan invert on*	126 – 128		49.4 – 50.2%	
		Zoom invert off*	129 – 131		50.6 – 51.4%	
		Zoom invert on*	132 – 134		51.8 – 52.5%	
		No function	135 – 140		52.9 – 54.9%	
		Focus tracking off*	141 – 143		55.3 – 56.1%	
		Focus tracking near*	144 – 146		56.5 – 57.3%	
		Focus tracking medium*	147 – 149		57.6 – 58.4%	
		Focus tracking far*	150 – 152		58.8 – 59.6%	
		No function	153 – 158		60.0 – 62.0%	
Framing Control = PI Mode, (position/Index)*	159 – 161	62.4 – 63.1%				
Framing Control = LR Mode, (left/right)*	162 – 164	63.5 – 64.3%				
No function	165 – 191	64.7 – 74.9%				
Lamp power Eco*	192 – 194	75.3 – 76.1%				
Lamp power Normal*	195 – 197	76.5 – 77.3%				
No function	198 – 200	77.6 – 78.4%				
Auto lamp on enabled*	201 – 203	78.8 – 79.6%				
Auto lamp on disabled*	204 – 206	80.0 – 80.8%				
No function	207 – 209	81.2 – 82.0%				
Lamp on*	210 – 212	82.4 – 83.1%				
Lamp off*	213 – 215	83.5 – 84.3%				
No function	216 – 245	84.7 – 96.1%				
Reset pan/tilt only *	246 – 248	96.5 – 97.3%				
Reset head only*	249 – 251	97.6 – 98.4%				
Reset all*	252 – 255	98.8 – 100%				

* Hold value for 3 seconds to apply

Notes:

Percentage values are calculated by dividing DMX values by 2.56 and rounding to the nearest 0.1%.

To apply a command on the Special/Control channel, send the corresponding DMX value for the indicated time (3 seconds).

Default settings are written in **bold type**.

PRELIMINARY

PRELIMINARY

