









TECHNICAL DATA

| 20 RackMount | |
|------------------------|--|
| 1GB Ram | |
| 128GB SSD | |
| 5" touchscreen display | |

CONTROL

| Universes | 256 |
|-----------|----------------|
| Addresses | 131,072 |
| Protocols | WS2811, WS2812 |
| | SK6812, WS2813 |
| | WS2812b |
| | |

Astro time clock schedule control

OPERATING CONDITIONS

| Variable power | |
|----------------|-----------|
| supply (240V) | 200 Watts |

DIMENSIONS & WEIGHT

| Depth | 13" (33 cm) |
|--------|-------------------|
| Width | 16" (40.6 cm) |
| Height | 3.5" (8.9cm) |
| Weight | 14.8 lbs (6.7 kg) |

INPUT/OUTPUT

| 1x Ethernet (In) | SACN, ArtNet |
|--------------------|------------------|
| 16x Ethercon (out) | STP/UTP Ethernet |

FEATURES

- -Easily modify control manager configurations and settings via 5" touchscreen or network web browser.
- -Built in presets and macros for on the fly show control.
- -Save show files directly to the internal SSD Card for playback, no need for a secondary PC.
- -Signal distribution to Pixelizer reciever cards can be placed up to 1,500' feet away from the PixeLit Control Manager.