



## Preliminary Data

### Key Facts

- 40 W RGBL LED from X5 Series at up to 20 W power
- innovative Twist-Zoom-Mechanism
- super compact low weight with only 580 g

## The compact mini-washlight

The X5 Dot Wash is an extremely compact mini-washlight and has been designed to solve the problem of getting great light quality and high CRI from a small LED based fixture that is no larger than an MR16 Birdie.

The GLP X5 Dot Wash uses a 40W RGBL LED from the impression X5 Series to give high CRI across a large color gamut and has been critically acclaimed across the theatrical and televisual markets. Its small body and sleek design allow it to be tucked into small locations – whether seen or unseen.

It features 16-bit color control and an color match to the X5 Series. The integrated exclusive Twist-Zoom-Mechanism allows manual zoom from 16 to 68 degrees without altering the fixture's body. Its IP65 rating ensures plenty of use options. The X5 Dot runs on 24 – 48 V DC from any external power source and can run wirelessly or wired for data.

If people prefer the classic birdie look, the optional accessory adapter fits any existing accessories.

## Technical Data (1/2)\*

### LIGHT SOURCE

Type	RGBL LED
Power	10 – 20 W
Count	1

### OPTICAL SYSTEM

Output	up to 550 lm
Max. Peak Luminous Intensity	4.58 kcd
Min. Zoom	16°
Max. Zoom	68°
Zoom Ratio	1:5
Light aperture diameter	50 mm / 1.96 in

### DYNAMIC EFFECTS

Dimmer	16 bit
--------	--------

# Technical Data (2/2)\*

## CONTROL & PROGRAMMING

DMX Channels	tbd
Control Modes	tbd
Protocols	DMX (USITT DMX512-A)   RDM (ANSI/ESTA E1.20)   GLP iQ.Mesh
High-Res Channels	Dimmer
Setting and addressing	DMX   RDM   GLP iQ.Mesh
Firmware Update	DMX Link via DProg   GLP iQ.Mesh   GLP iQ.Tool

## CONNECTIONS

Power & Signal connection	Combined Power/Data Cable Tail, 750 mm; with XLR 4-Pin connector male
---------------------------	---

## ELECTRICAL SPECIFICATIONS

Power input	24 – 48 V DC
Power supply unit	external, not included

## THERMAL SPECIFICATIONS

Cooling Type	convection
min. ambient temperature	-10 °C / 14 °F
max. ambient temperature	45 °C / 113 °F
Thermal Protection	automatic
Total heat dissipation	70 BTU/h

## INSTALLATION

Mounting	2x 3/8" and 1/4" 20 UNC thread   combined hanging / floorstand yoke
Orientation	Any   horizontal sideway   vertical hanging
Location	Indoor   Outdoor

## CONSTRUCTION

Housing color	Black   optional: White
Material	High-impact flame-resistant thermoplastic   Aluminum
Protection Rating	IP65

## DIMENSIONS & WEIGHT

Weight netto	580 g / 1.28 lbs
--------------	------------------

## ARTICLE NUMBERS

X5 Dot	7725
--------	------

\* Preliminary Data.  
Subject to change.